

Automatic Tire Changer TP823GDR



Precision and Durability

Revolutionize your tire changing process. Our advanced tire changer is engineered for efficiency, offering an extra-long, low-cabinet design ideal for large tires. Enjoy superior versatility with an adjustable 29" clamp, robust manganese steel construction, precise variable speed control (0-12 RPM), and exceptional clamping and bead breaking power with quick-release action.



TP 823GDR



10" - 26"



12" - 29"



13,7"
(350 mm)



43"
(1080 mm)



Motoinverter
0 - 12 RPM



Key features

- Extra Long cabinet to optimize target large tire with Low cabinet design
- Adjustable Clamp up to 29" rim
- Durable Manganese Steel Components
- 0-12 RPM (Variable Speed)
- Extra Force clamping force and bead breaker force
- Quick Release Bead breaker function
- HELP Assist Arm in standard configuration

Technical specification

Turntable speed	0 - 12 RPM
Outer clamping range	10" - 26"
Inner clamping range	12" - 29"
Max tire width	13,7" / 350 mm
Max tire diameter	43" / 1080 mm
Working air pressure	8 - 10 bar
Bead breaker force	2500 - 3000 kgf
Nett / Gross weight	345 / 380 kg
Packing size - tire changer	1150x800x1000 mm
Packing size - assist arm	1150x520x300 mm
Power supply	230V 50Hz 1Ph

Standard accessories

- 1x inflation gauge
- 1x crowbar
- 1x mounting head gasket
- 1x lubrication box
- 1x plastic shovel protector
- 1x plastic mounting head protector
- 1x plastic jaw protector